

DATA SHEET SWISSCAVE WLI-90DF

Technical Data

Exterior	
Casing	Black coated steel
Door glazing	Fully glazed UV-resistant, gas-filled, with low energy panes equipped glass door (double glazed)
Door frame	Filigree edging made of black anodised, brushed aluminium
Door handle	Anodised, brushed aluminium (rectangular)
Door lock	Yes
Door hinge	Right
Door hinge convertible as option (right to left)	Yes
Product dimensions without door handle (H/W/D)	595 x 590 x 565 mm
Packaging dimensions (H/W/D)	625 x 655 x 640 mm
Interior	
Temperature zones	2
Lighting	all around illumination white, blue, amber (adjustable)
Lighting on/off switch	Yes
Number of shelves total	4
Number of display shelves (for perfect wine presentation)	0 (other shelf types)
Number of bottle levels max.	5
Shelf material	Raw natural sapele (Mahogany) wooden display shelves with attractive grip bars
Telescopic shelves on extendable steel ball bearings	Yes
Inside casing	Black PUR
Scope of functions	
Optimal usage	Tempering and storing
User interface	2 digital displays (set and actual temp. changable)
Active carbon filters (ensuring optimal air quality)	Yes
Compressor	JP-STD
Coolant	R600a (environment friendly)
Vibrationfree implementation	Yes
Cooling system	Combined fan and convection cooling
Defrost function	Automatic
Temperatur Memory Function (Power failure)	Yes
Condensation water container	Yes
Acoustic temperature alarm	Yes
Acoustic door alarm	Yes
Tilt protection	Yes
Feet adjustable to compensate uneven floors	Yes

Performance data	
Bottle capacity (Bordeaux shape, part of shelves removed)	29
Bottle capacity (Bordeaux shape, all shelves inserted)	26
Space for oversized bottles (Magnum, 3lt.)	Yes (by removing 1 shelf)
Humidity	Recommendation 50-70%
Climate classification	SN-T
Volume	69 l
Noise level	39 dB(A) sound-absorbing recommendation
Temperature range	5 °C - 16 °C 9 °C - 20 °C 1 °C - 2 °C

General Information	
Cooler shape	Kitchen-built-in
Maintenance contract (warranty extension)	Recommended
Transport weight	39 kg
Net weight	37 kg
Power consumption per day	0.411 kWh (ca.)
Voltage	220 V / 50 Hz
Cable length	2 m





SWISSCAVE WLI-90DF



150 kWh/annum



27



38dB
ABCD

2016/06/10
9102/01/01