

DATA SHEET SWISSCAVE WLI-160DF

Technical Data

Exterior		Performance data	
Casing	Black coated steel	Humidity	Recommendation 50-70%
Door glazing	Fully glazed UV-resistant, gas-fil- led, with low energy panes equip- ped glass door (double glazed)	Actively managed humidity (adjustment range 60-80%)	
Door frame	Frameless (all glass)	Climate classification	SN-T
Door handle	Anodised, brushed aluminium	Volume	100 I
Door lock	Yes	Noise level	39 dB(A) sound-absorbing re- commendation
Door hinge	Right		5 °C - 20 °C 5 °C - 20 °C
Door hinge convertible as option (right to left)	Yes	General Information	
Product dimensions without door handle (H/W/D)	886 x 590 x 560 mm	Cooler shape	Kitchen-built-in
Packaging dimensions (H/W/D)	975 x 655 x 640 mm	Maintenance contract (warranty extension)	Recommended
Interior		Transport weight	51 kg
Temperature zones	2	Net weight	47 kg
Lighting	All around illumination white, blue, amber (adjustable)	Power consumption per day	0.427 kWh (ca.)
Lighting on/off switch	Yes	Voltage	220 V / 50 Hz
Number of shelves total	5	Cable length	2 m
Shelf material	Raw natural sapele (Mahogany) wooden display shelves with attractive grip bars		
Telescopic shelves on extendable steel ball bearings	Full extension shelves (80%)		
Inside casing	Black PUR		

Scope of functions

Optimal usage	Tempering and storing	
User interface	2 digital displays (set and actual temp.)	
Active carbon filters (ensuring optimal air quality)	Yes	
Compressor	JP-HE (high efficent)	
Coolant	R600a (environment friendly)	
Vibrationfree implementation	Yes	
Cooling system	Combined fan and convection cooling	
Temperatur Memory Function (Power failure)	Yes	
Condensation water container	Yes	
Heating	Powerful winter heating function (*In heating mode, temperature and humidity values may vary from the set value)	
Acoustic temperature alarm	Yes	
Acoustic door alarm	Yes	
Feet adjustable to compensate uneven floors	Yes	



