

DATA SHEET SWISSCAVE WLB-460FLD-MIX

Technical Data

iecnnicai Data			
Exterior		Performance data	
Casing	Black coated steel	Humidity	Recommendation 50-70%
Door glazing	Fully glazed UV-resistant, gas-fil- led, with low energy panes equip- ped glass door (3-layer glazing)	Actively managed humidity (adjustment range 60-80%)	
Door frame	Filigree edging made of black anodised, brushed aluminium	Climate classification	SN-T
Door handle	Anodised, brushed aluminium (optionally available)	Volume	379
Door lock	Yes	Noise level	38 dB(A) sound-absorbing re- commendation
Door hinge	Right	Temperature range	5°C - 20°C
Door hinge convertible as option (right to left)	Yes	General Information	
Product dimensions without door handle (H/W/D)	1720 x 595 x 725 mm	Cooler shape	Free-standing or embeddable with shadow gap
Packaging dimensions (H/W/D)	1750 x 630 x 762 mm	Maintenance contract (warranty extension)	Recommended
Interior		Transport weight	125 kg
Temperature zones	1	Net weight	110 kg
Lighting	All around illumination white, blue, amber (adjustable)	Power consumption per day	0,378 kWh (ca.)
Lighting on/off switch	Yes	Voltage	220 V / 50 Hz
Number of shelves total	7	Cable length	2 m
Shelf material	Raw natural sapele (Mahogany) wooden display shelves with attractive grip bars		
Telescopic shelves on extendable steel ball bearings	Full extension shelves (80%)		
Inside casing	Black PUR		
Scope of functions			
Optimal usage	Long-term storage and aging		





